

EGL5055



Independent I/O with Exchangeable Media Board Solution

Features

- Intel® Atom™, Celeron®
- 1 x DDR3L SO-DIMM, up to 8GB
- 2 x SATA with Pin 7 VCC
- Up to 8 x USB + 6 x Serial Ports
- 3MB NVM up to 8MB
- 6 x Door Intrusion Log
- 32 x Isolation GPI + 32 x High Current GPO
- 1 x VGA
- Modular I/O Design
- Mini-ITX Form Factor
- NVIDIA 1050Ti Graphic Card
- 2.5" SSD Bay with Detection Log
- Lifetime Support until 2029

Headquarter

10F-3, No. 270, Sec. 4,
Chung Hsiao E. Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com

EFCO
EverFine Group

Note : All product specifications are subject to change without notice

EGL5055

Asia Pacific

10F-3, No. 270, Sec 4, Chung Hsiao
E. Road, Taipei, 10694, Taiwan
Phone: +886-2-2751-7192
Email: info@efco.com.tw

EMEA

Ulrichsberger Str. 17, Haus G1,
94469 Deggendorf, Germany
Phone: +49-991-2009298-0
Email: sales@efcotec.de

Americas

570 W. Cheyenne Ave., Suite 210,
North Las Vegas, NV 89030
Phone: + 1-702-848-5320
Email: sales-us@efcotec.com

UK & Ireland

Phone: +44 (0) 7976-155552
Email: sales-uk@efcotec.com

| Model | Description |
|---------------|---|
| EGL5055-2 | <ul style="list-style-type: none">• Intel® Atom® E3825 Dual Core, 1.3GHz, 1MB L2Cache)• 1 x DDR3L-1067 SODIMM up to 8GB• 2 x SATA with Pin 7 VCC |
| EGL5055-N2930 | <ul style="list-style-type: none">• Intel® Celeron® N2930 Quad Core, 2.16GHz, 2MB Cache• 1 x DDR3L-1333 SODIMM up to 8GB• 2 x SATA with Pin 7 VCC |
| EGL5055-J1900 | <ul style="list-style-type: none">• Intel® Celeron® J1900 Quad Core, 2.42GHz, 2MB L2Cache• 1 x DDR3L-1333 SODIMM up to 8GB• 2 x SATA with Pin 7 VCC |

Headquarter

10F-3, No. 270, Sec. 4,
Chung Hsiao E. Rd.,
Taipei, 10694, Taiwan

T +886 2 2751-7192
E-mail: info@efco.com.tw

EMEA

T +49-991-2009298-0
E-mail: info@efcotec.com

America

T +1-760-827-8600
E-mail: sales-us@efcotec.com



Note : All product specifications are subject to change without notice